

# CFX SOVEREIGN WHITE & BASE **Medium Solids Waterbased Inks**

### **Technical Data Sheet**

REV. 20240310

### **Key Features**

A Medium Solids, PVC, Phthalate and Formaldehyde free aqueous ink system optimized for automatic printing.

The Sovereign series has exceptional soft hand feel, great elasticity and high opacity with a smooth, matt, tack free surface.

Formulated as a high productivity ink system with excellent open-time that allows for multi-colour printing without the need for multiple flashing.

### **Wash Resistance**

Sovereign inks when correctly cured will pass most specifier wash tests. For more stringent wash tests the use of a crosslinker is recommended. No testing should be carried before a minimum of 24 hours after curing.

### Compliance

All CFX Aqueous ink are formulated to be Phthalate Free, meet Oekotex standards and do not contain any Substances of Very High Concern. Currently ,we, the manufacturer, do not test for compliance and should the user require certification we recommend they use an independent test house for verification

### **Storage**

Avoid direct sunlight and extremes of temperature.

### **Health and Safety**

Please refer to the appropriate MSDS sheet

### **Application Recommendations**

### **Fabric Types**

Suitable for all types of fabric, on Cotton / Polyester blends and 100% Polyester we recommend the use of Barrier Grey underbase to prevent dye migration

### Mesh

From 43 to 72 threads per cm

Water resistant Photo-Emulsion

### Squeegee

Square Profile. 75/90/75 triple durometer.

### **Additives**

Water based inks can dry on the screen too quickly in low humidity situations. The addition of 2-5% of CFX Stellar Open Time Extender should resolve this issue.

To improve wash fastness and reduce surface tack we recommend 0.5 - 2.0% of CFX Stellar Cross linker.

### Flash Temperature / Gel Point

Maintaining a pallet temperature of 65°C / 150°F will maximize productivity on Multicolor designs. We recommend flash cures with hot air assistance for maximum efficiency.

### **Cure Temperature**

160°C / 320°F for 120 to 150 seconds

### Clean Up

For equipment use a Biodegradable Screen Wash. Clean up spills with a suitable absorbent material. Dispose of unused ink responsibly in accordance with local regulations

## **Suggested Mixes**

	Dark Shade Mix	Medium Shade Mix	Light Shade Mix
Sovereign Clear	80-90%	50-60%	20-30%
Sovereign White	10-20%	40-50%	70-80%
Aquatint Pigment Emulsion	6-8%	5-6%	2-4%

Disclaimer - Not all of our products are available in every Country - please check with our Sales Team for availability. The data presented in this bulletin is based on our current state of knowledge but does not absolve the user from carefully checking the product on receipt. We reserve the right to make changes on the basis of product improvement and raw material availability. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.